

AMITEK PURE ACRYLIC EMULSION

Physical Parameters:

Appearance	: Milky White Emulsion
pH (As Such)	: 50 ± 0.5%
Solid Content (150°C/20 min)	: 9.0-10.0
Viscosity (Brookfield LVF # .2/60 @ 25 °C)	: 200 cps max
Particle Size	: 0.1-0.12micron
Specific Gravity	:1.0-1.2 gm/cc
Film Clarity	: Clear free from bits

Typical Properties:

- High gloss & pigment binding, color retention properties
- Excellent scrub resistance
- Excellent resistance to chemicals, alkali, acid, salt water, dirt pick up, abrasion, chalk
- Good divalent ions & pH stability
- Paints made with amitek emulsion dry quickly.

Recommended Uses:

- Specially for high gloss & abrasion resistant exterior paint, elastomeric coatings.
- Premium quality exterior wall paints
- Road marking paints & floor paints

Advantages:

Offer additional advantages from the standpoint of toxicity, fire hazards, ease of clean up and air pollution control laws.

DISCLAIMER:

The information above is believed to be accurate & represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use, handling and from contact. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way, Amitek Infra will be liable for any claims, losses, or damages of any third party or for lost any special, indirect, incidental, consequential or exemplary charge, however arising, even Amitek Infra has been advised of the possibility of such damages.